

NYLOK® TORQ-PATCH® LOCKNUT

Prevailing Torque Locking Element

NYLOK® TORQ-PATCH® locknut is a self-locking element comprised of nylon permanently bonded into the threads of a nut. When the NYLOK® TORQ-PATCH® locknut is engaged it creates a wedge between the nut and mating part compressing the nylon and creating metal to metal contact opposite the patch. This metal to metal contact results in a positive resistance to vibration and loosening. Since nylon has great memory characteristics, this locking element can be reused several times.



Technical Data – NYLOK® TORQ-PATCH® Locknut

- Color — blue/red (special colors available upon request)
- Dry Wedge — immediate locking
- Temperature Range -56°C (-70°F) to +121°C (+250°F)
- Shelf-Life indefinite
- NYLOK® TORQ-PATCH® locknut is also referred to as TUF-LOK®

Typical Performance Results (M10 plain finish)

- Prevailing-On Torque 5.0 – 10.0 Nm
- First Removal Prevailing-Off Torque (without preload) min. 2.5 – 5.0 Nm
- Fifth Removal Prevailing-Off Torque min. 1.8 – 2.8 Nm

Advantages

- Reusable/adjustable
- Exceptional vibration resistance
- Resistant to lubricants, fuel, hydraulic fluids and most commercial solvents
- Can be applied to any size or thread configuration larger than a M6/1/4" nut
- Bonds to a broad range of fastener finishes

(continued)

INNOVATION™

Every fastening task comes with its own set of challenges – locking, sealing, high temperatures, thread contamination or any combination of these. When these challenges slow product development of the design process, Nylok engineers provide INNOVATION™ services – the knowledge and resources to uncover solutions that balance cost, manufacturability and environmental concerns.

As a supply chain partner, Nylok products serve a global network of customers in a diverse range of industries – automotive, aerospace/defense, heavy machinery/truck, electronics, weaponry and specialty applications. Nylok solves fastener problems from NASA applications to the small home appliance industry, processing more than 10 billion parts per year – the global leader in fastener processing.





NYLOK® TORQ-PATCH® LOCKNUT

Prevailing Torque Locking Element

Advantages (continued)

- Complies with or exceeds IFI, DIN and major OEM specifications
- Provides a seal for threads
- Parts are ready for assembly
- Precise thread coverage in every part
- Is not affected by high humidity conditions
- Environmentally friendly/non-toxic
- 180° (standard) or 360° (optional) radial coverage
- Torque can be adjusted to meet specific applications
- Cost effective
- No metal removal to reduce fastener strength or performance

COMPANY NAME	SPECIFICATIONS
CHRYSLER	PF-6180
FORD	WE950
GM	GM6189P GMW16722
MILITARY	MIL - DTL - 18240F NASM25027
CATERPILLAR	IE-2511
IFI	IFI - 100/107 IFI - 155 IFI - 555 IFI - 560



World Headquarters and Research & Development

15260 Hallmark Court
Macomb, MI 48042-4007
586.786.0100
sales@nylok.com
nylok.com

Manufacturing Facilities

Michigan

Macomb, MI 48042-4007
586.786.0100 | 800.826.5161
ISO 9001:2008
nylok.com

California

Anaheim, CA 92801-6738
714.635.3993 | 888.226.9565
ISO 9001:2008
QPL 18240
QSLM Approved
aerospacenylok.com

Illinois

Lincolnwood, IL 60712-3985
847.674.9680 | 800.446.5956
ISO 9001:2008
QPL 18240
nylok.com

New Jersey

Hawthorne, NJ 07507-0651
973.427.8555 | 800.276.9565
ISO 9001:2008
QPL 18240
aerospacenylok.com



A Marmon/Berkshire Hathaway Company